

ONDUTEX®



Non-woven screening material for underground protection and drainage of alleys.

Benefits

- Avoid weed growth and roots.
- Avoid collaps of alleys.
- Protect paths.
- Facilitate drainage.

Technical characteristics & range

ONDUTEX®										
Weight per m ²	100 g/m ²								180 g/m ²	300 g/m ²
Dimensions	0,70 m x 60 m	2,00 m x 10 m	1,00 m x 10 m	1,00 m x 20 m	2,00 m x 25 m	20 m x 1 m	10 m x 2 m	25 m x 2 m	20 m x 1 m	20 m x 2 m
White (EAN)	3467670009677	3467670010376	3467670009714	3467670009684	3467670009707	-	-	-	-	-
Grey (EAN)	-	-	-	-	-	3467670023376	3467670023383	3467670024953	3467670022966	3467670022973
Norm	Comply with EN 13252 CE									

Installation instructions

Pedestrian paving paths

- 1 Create a 10 to 20 cm recess in the ground, depending on the type of paving used. Even out any slope and compact.



- 2 Unroll the geotextile and spread a coat of sand at least 5 cm thick over it.




- 3 Tap in and adjust the paving using a rubber mallet.



Gravel alleys

- 1 Create a 10 cm recess in the ground. Even out any slope and compact.



- 2 Unroll the geotextile and spread a coat of gravel at least 5 cm thick over it.



- 3 Enjoy your new long-lasting gravel alley.

